

## Geneva

An unconventional diverse rigid core construction, conveying an innovative design



### Physical Construction

Construction	SPC (Solid PVC Core)
Finish	UV Cured Urethane with Ceramic Bead
Installation Method	Unilin Click
Size	7" x 48" nominal
Wear Layer Thickness	20 mil
Overall Thickness	5.5mm
SPC Core Thickness	4 mm
Attached Cushion	1.5 MM IXPE Attached Cushion Made from Virgin Materials Closed Density 66 kg/m3
Pieces per Carton	8
Carton Quantity	18.91 sf
Carton Weight	32.8 lbs
Cartons per Pallet	65
Pallet Quantity	1,229.15 sf
Pallet Weight	2,182 lbs

### Performance

Critical Radiant Flux	ASTM E 648-10
Thickness	ASTM F 386
Size and Squareness	ASTM F 2055
Flexibility	ASTM F 137
Residual Indentation	ASTM F 1914-07
Resistance to Heat	ASTM F 1514-04
Resistance to Chemicals	ASTM F 925-02
Dimensional Stability	ASTM F 2199-09

### Warranties

Ltd. 25 Year Residential Wear Warranty  
 Ltd. Lifetime Structure Warranty  
 5 Year Light Commercial



01 Urban Castle



02 Boho Chic



03 Woodland Frost



04 Studio Gray



\*\*Specifications are based on averages from manufacturing process and may vary within normal industry tolerances. Components may be changed without notice due to raw material shortages and/or technological improvements. Such variances do not affect performance.\*\*