



TuffCore Technical Specs

Color #820-#824

Description: National Flooring Products Laminate with Attached IXPE
Warranty: RES: Lifetime COM: 10 Year
Installation: Float
Size/Packaging:
Construction: 0.15mm - Top Layer (Overlay + décor melamine impregnated paper)
 11.7mm – High Density Fiber Board Core (860kg/m3)
 0.15mm - Balance Layer (Melamine impregnated paper)
 1.5mm - Attached IXPE
TOTAL Thickness: 13.5mm

Bevel: 4 side painted micro bevel
Locking System: EZ Drop
Bevel: 4 side painted micro bevel

TEST DATA:

CARB	ASTM D6007: PASS CARB PHASE 2 EN 717-1: EO	Impact Sound Reduction	IIC
VOC	ISO 16000: VOC A / AgBB U Mark Cert.	Sound Transmission Reduction	STC
Ortho-phthalates	Prop 65 Compliant	Thermal Resistance (R-Value)	0.103 m2-K?W
PCP	EN 12673: Pass	Reaction to fire	EN 13051-1: Pass
SVHC	REACH Compliant	Wear resistance	EN 13329: 4000 Cycles AC 3
Dimensional Variation	Pass	Slipperiness	ASTM C1028: 0.5
Swelling after submersion in water	Class 33, Heavy Commercial 11%	Resistance to staining	EN 438-2: Class 34, Heavy Commercial

COUNTRY OF ORIGIN: China

CERTIFICATIONS: Indoor Air Quality Certified, French VOC

